

DESCRIPTION

ENEOS Performance Oil is a highly refined, mineral based engine oil recommended for gasoline and diesel engines. High-viscosity index and selected base oil assures an excellent cold start with outstanding lubricating film at high-temperatures. The specially chosen additive enhances performance and functions of the engine, prolonging its operational life. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine for daily condition.

ADVANTAGES

√ **Exceptional Performance Engine Oil**

Blended with highly refined high-viscosity index mineral base oils and optimised additives, its high-temperature oxidation stability is superior compared to conventional engine oils made from other mineral base.

√ **Reducing Fuel Consumption**

Helps reduce the fuel consumption as well as emission levels. Due to the unique formulation, low evaporation under severe operating condition is assured.

√ **Exceptional Resistance for Wear, Corrosion, Foaming and Oxidation**

Gives optimum protection against wear, provides strong anti-corrosion and anti-foam characteristics as well as high resistance against oxidation.

PERFORMANCE LEVEL

SN/CF

APPLICABLE VEHICLES

Recommended for all range of engines in cars and light commercial vehicles with gasoline and diesel engine. Suitable for Japanese and European automobiles.

CONTAINER SIZE

1 Litre

4 Litre

209 Litre

TYPICAL CHARACTERISTICS

SAE Grade		10W-30	15W-40	20W-50
API Performance Grade		SN/CF	SN/CF	SN/CF
ILSAC Performance Grade		GF-5	GF-5	-
Density (15°C) g/cm ³	ASTM D 4052	0.8686	0.8743	0.8832
Viscosity mm ² /s	(40°C) ASTM D 445	63.07	100	157.8
	(100°C) ASTM D 445	9.89	13.76	18.16
Viscosity Index	ASTM D 2270	141	139	128
Flash Point °C	ASTM D 92	234	236	242
Pour Point °C	ASTM D 97	-39.0	-33.0	-30.0
Base Number	ASTM D 4684	5.87	5.99	6.18

Note: Typical characteristics are subject to change without notice (July, 2017)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils.
- In case of physical contact, wash immediately with soap and water.
- Protect the environment by disposing off used oils as per local regulations